


LEVEL 2 ROAD, TYPE A OR TYPE B WORKS	
DESIGN PARAMETERS	
SPEED LIMIT	50 or 60km/h
SIGN VISIBILITY (m)	50
NUMBER OF SIGNS	3
CUMULATIVE DISTANCE(m)	75
DISTANCE BETWEEN ADVANCE SIGNS(m)	25
TAPER AT LANE	45°
TAPER AT HARD SHOULDER(m)	N/A
LAMP SPACING AT TAPER(m)	6
LONGITUDINAL LAMP SPACING(m)	12
CONE SPACING AT TAPERS(m)	3
LONGITUDINAL CONE SPACING(m)	6
CONE HEIGHT(mm)	750
LONGITUDINAL SAFETY ZONE(m)	25
LATEAL SAFETY ZONE(m)	0.5
MINIMUM LANE WIDTH(m)	3.0

NOTES:



NOTES:
 1) ALL WORKS ARE TO BE CARRIED OUT IN ACCORDANCE WITH LOCAL AUTHORITY REQUIREMENTS AND THE ROAD WORKS ACT (1997).
 2) ALL WORKS ARE TO BE CARRIED OUT IN ACCORDANCE WITH LOCAL AUTHORITY REQUIREMENTS AND THE ROAD WORKS ACT (1997).
 3) INSTALLATION, MAINTENANCE AND REMOVAL OF TEMPORARY TRAFFIC CONTROL SIGNS SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR.
 4) CONTRACTOR IS TO CARRY OUT A SITE RISK ASSESSMENT PRIOR TO THE COMMENCEMENT OF WORKS AND TO REFLECT THE RESULTS OF THE ASSESSMENT IN THE SITE-SPECIFIC SAFETY & HEALTH PLAN.
 5) CONTRACTOR IS TO CARRY OUT A SITE RISK ASSESSMENT PRIOR TO THE COMMENCEMENT OF WORKS AND TO REFLECT THE RESULTS OF THE ASSESSMENT IN THE SITE-SPECIFIC SAFETY & HEALTH PLAN.



WR 025
 WR 026
 SITE ACCESS TO LEFT/RIGHT
 THESE SIGNS SHOULD BE USED TO INDICATE THE POSITION OF A SITE ENTRANCE AND/OR EXIT TO THE WORKS AREA.
 SITE ACCESS CHANGES AND/OR EXIT LOCATIONS TO BE AGREED BY THE TPO ON SITE.



CLIENT REF:
 KN REF:
 LOCATION: CLONSHAUGH ROAD
 DATE: 17/09/12

www.kms.ie
 2-4 Clonsilla Avenue
 Clonsilla
 Dublin 22
 Tel: 003 457 5000
 Fax: 003 457 5001
 Email: info@kms.ie
 Web: www.kms.ie