

NOTES:

- THIS DRAWING IS TO BE READ IN CONJUNCTION WITH ALL OTHER RELEVANT ENGINEERING DRAWINGS. ANY DISCREPANCIES, ERRORS OR OMISSIONS TO BE BROUGHT TO THE ATTENTION OF THE DESIGNER.
- ALL DIMENSIONS, LEVELS AND LOCATIONS OF EXISTING SERVICES AND CELLARS TO BE CHECKED AND CONFIRMED BY THE CONTRACTOR ON SITE PRIOR TO COMMENCEMENT OF WORKS.
- EMPLOYER'S REPRESENTATIVE TO BE INFORMED BY THE CONTRACTOR OF ANY DISCREPANCIES PRIOR TO COMMENCEMENT OF WORKS ON SITE.
- DESIGN BASED ON TOPOGRAPHICAL, GPR AND CELLAR SURVEYS AND RECORDS PROVIDED BY DCC.
- CONTRACTOR TO ENSURE PROPOSED GULLY OUTLET PIPE PROMOTES POSITIVE DRAINAGE OF GULLY (MINIMUM GULLY OUTLET PIPE GRADIENT TO BE 1:100).
- SEALED/TRAPPED GULLIES SHALL BE USED.
- SURFACE WATER & FOUL SEWER PIPES LESS THAN 1.2m BELOW THE ROAD SURFACE SHOULD BE PROTECTED FROM DAMAGE BY PROVIDING AN ST4 CONCRETE HAUNCHING TO CC-SCD-06921 TYPE Z ENCASEMENT.
- PLEASE REFER TO SERIES 200 DRAWINGS REMOVAL OF GULLIES & CHAMBERS AND ALSO READJUSTMENT OF MANHOLE COVER LEVELS.
- NO LIABILITY IS ACCEPTED FOR ANY DISCREPANCY, OMISSION OR DEVIATION AND THE ACTUAL POSITION OF MAINS AND SERVICES MUST BE VERIFIED AND ESTABLISHED ON SITE BEFORE ANY MECHANICAL EXCAVATING PLANT IS USED.
- THE INFORMATION IS SUPPLIED WITHOUT PREJUDICE AND DOES NOT RELIEVE THE CONTRACTOR OF HIS RESPONSIBILITY TO CONTACT EACH OF THE RELEVANT UTILITY COMPANIES DIRECTLY AND TO SATISFY THEMSELVES OF THE LOCATIONS OF ALL SERVICES AND CELLARS PRIOR TO COMMENCEMENT OF WORKS.
- FINAL POSITIONS OF MANHOLES / GULLY PITS TO BE FINALISED ON SITE WITH THE RESIDENT ENGINEER.
- CONTRACTOR TO REFER TO SPECIFICATION APPENDIX 5/1 FOR DETAILS.
- CONTRACTOR TO UNDERTAKE DRAINAGE WORKS IN ACCORDANCE WITH THE GREATER DUBLIN REGIONAL CODE OF PRACTICE.
- CONNECTIONS TO EXISTING CULVERT TO BE UNDERTAKEN BY IRISH WATER.

IMPORTANT
SAFETY, HEALTH & ENVIRONMENTAL
INFORMATION


HAZARD WARNING

CONDITION OF EXISTING BRICK ARCHED CULVERT IS UNKNOWN. CONTRACTOR TO UNDERTAKE CCTV SURVEY OF EXISTING CULVERT TO CONFIRM CONDITION OF CULVERT, AND PROVIDE A RISK ASSESSMENT AND METHOD STATEMENT PRIOR TO COMMENCEMENT OF DRAINAGE WORKS.

THIS IS NOT A COMPLETE LIST OF HAZARDS

NOTE:
CONTRACTOR TO CONFIRM ALL EXISTING LEVELS ON SITE PRIOR TO CONSTRUCTION

- KEY:**
- NG ** PROPOSED STEEL GULLY TO CONFORM TO EN 124, CLASS D400 OR EQUIVALENT
 - G ** EXISTING GULLY TO BE RETAINED IN PLACE. NEW GRATING TO BE FITTED, TO CONFORM TO EN 124, CLASS D400 OR EQUIVALENT
 - EXISTING MANHOLE / GULLY PIT
 - PROPOSED GULLY PIT
 - PROPOSED TYPE B MANHOLE
 - PROPOSED GULLY CONNECTION (150mm DIAMETER UNLESS STATED OTHERWISE)
 - EXISTING COMBINED SEWER (TAKEN FROM EXISTING RECORDS)
 - EXTENT OF EXISTING BRICK CULVERT TO BE CCTV SURVEYED IN ACCORDANCE WITH SPECIFICATION APPENDIX 29/1



PROJECT
Fitzwilliam Cycle Route



Project Ireland 2040
Building Ireland's Future

CONSULTANT
AECOM
Adelphi Plaza
George's Street Upper
Dun Laoghaire Co.Dublin
Tel:+353(0)1 2383100 Fax:+353(0)1 2383199
www.aecom.com

ISSUE/REVISION

A/R	DATE	DESCRIPTION
A	JUNE 2022	ISSUED FOR TENDER

KEY PLAN

PROJECT NUMBER
60578028

SHEET TITLE
DRAINAGE
SHEET 1 OF 6

SHEET NUMBER
60578028_DD_SHT-500.1

This drawing has been prepared for the use of AECOM's client. It may not be used, modified, reproduced or relied upon by third parties, except as agreed by AECOM or as required by law. AECOM accepts no responsibility, and denies any liability, whatsoever, to any party that uses or relies on this drawing without AECOM's express written consent. Do not scale this document. All measurements must be obtained from the stated dimensions.